


# PIKE

0404 (LM40400)



## Wood Series

Cross-section dimensions:




Go edgy and playful with a youthful approach on the classic of wood. The **PIKE** is the profile with the **most discreet light source** in the series, for a fresh yet inobtrusive visual presence that is particularly fit for social spaces, whether recreational or collaborative.

### Features

- Engineered from sustainably harvested and recycled hardwood, for superior mechanical quality and to bring out the natural wood texture.
- Designed to give a uniform light without hot spots with an Optiflex lens and an LED strip or PCB of 120 LEDs per meter or more.
- Custom length by sections of 2 to 144 inches (3.6m).
- Application guide for 10mm (3/8-inch) LED strip or less.
- The insert is Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Available in natural or oiled finishes, or in custom wood essences and tints.

### Options



### LED strip compatibility

Compatible with LED strips or PCBs up to **14mm** wide.

### Linear weight










1.275 lbs/ft, 1.898 kg/m (without lens or insert)
















# PIKE

## Components and accessories

# Wood Series

PROFILE	LENSES	ENDCAPS	BRACKETS	ACCESSORIES	LENGTH
 <p>PIKE wood enclosure with 0499 Alu heatsink <b>0404</b> (LM40400)</p>	 <p>9000 Clear <b>9547</b> (LM22960-7)</p>  <p>9000 Optiflex <b>9541</b> (LM22960-1)</p>  <p>9000 Opal <b>9543</b> (LM22960-3)</p>	 <p>PIKE, Stainless Steel <b>0414</b> (LM40414)</p>	 <p>Pike/Silo suspension kit with 15ft. aircraft cable <b>0422</b> (LM22320-81)</p>	 <p>1.5" stainless steel canopy kit for coax. wire (suspended) <b>4075</b> (LM22980-30)</p>  <p>5" canopy kit, fits standard 4" junction box <b>9484</b> (LM22980-21) ALU <b>9483</b> (LM22980-19) WHITE <b>9485</b> (LM22980-23) BLACK <b>9488</b> (LM22980-24) CHROME</p>  <p>7950 10" Canopy Kit <b>7950</b> (LM22840-50) ALU <b>7961</b> (LM22840-61) WHITE <b>7962</b> (LM22840-62) BLACK <b>7963</b> (LM22840-63) CHROME <b>7964</b> (LM22840-64) BRUSHED NICKEL</p>	<p>Custom length by sections of 12 to 144 inches (3.6m), in increments of 12 inches (30cm).</p>
<b>0404</b>		<b>0414</b>	<b>0422</b>		
PROFILE	LENS	ENDCAPS	BRACKETS	ACCESSORIES	LENGTH

## Lumen package

LUMEN PACKAGE *	COLOR TEMPERATURE	USAGE	POWER SUPPLY TYPE	NOTES
 <p>255 lm/ft, flex. 5/16" wide 12/24V Constant Voltage <b>LP3528120</b></p>  <p>308 lm/ft, flex. 5/16" wide 24V Constant Voltage <b>LP3528180</b></p>  <p>462 lm/ft, flex. 9/16" wide 24V Constant Voltage <b>LP3528240</b></p>  <p>650 lm/ft, rigid 1/2" wide, 350/700mA Constant Current <b>LP573052**</b></p>	 <p>Candle White <b>2400K</b></p>  <p>Soft White <b>2700K</b></p>  <p>Warm White <b>3000K</b></p>  <p>Bright White <b>3500K</b></p>  <p>Neutral White <b>4200K</b></p>	 <p>Indoor, dry (IP22) <b>IP22</b></p>	 <p>Non-dimmable <b>NO</b></p>  <p>ELV dimming <b>ELV</b></p>  <p>0-10V dimming <b>0-10V</b></p>	<p>* The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors. ** Only available in lengths of 1/2/3/4/5/6/8 feet.</p>
<b>IP22</b>				
LUMEN PACKAGE	COLOR TEMPERATURE (CCT)	USAGE	POWER SUPPLY TYPE	

# Notes

