




Project	
Type	
Contact	



Bongo 4M
1 Light Sources
4 in. | 2191 x M
Round | Fixed | Surface Mounted

Performance Options	9W	13W	18W	26W
Source Lumens	1199 lm	1627 lm	2056 lm	2855 lm
Delivered Lumens	378 lm x M	899 lm x M	1578 lm x M	2191 lm x M
Lumens / Watt	42 lm	69 lm	88 lm	84 lm
Current	250 mA	350 mA	500 mA	700 mA
CRI/CCT Multiplier	2700°K	3000°K	3500°K	4000°K
80 CRI	0.93	1.00	1.00	1.07
95 CRI	0.69	0.75	0.81	0.87



P4	BON4M	18	30	A	3	C	WS	O	12	O	D
Options	Model	Wattage	Kelvin	CRI	Beam	Lens	Color	Driver	Length	Installation	I.P. Rating
P4	BON4M:Bongo 4M	09:09W 13:13W 18:18W 26:26W	27:2700° 30:3000° 35:3500° 40:4000°	A:80 B:95	1:10° 2:24° 3:36° 6:60°	C:Clear F:Frosted P:Prismatic S:Solite	WS:Matte White BK:Matte Black WK:White / Black Inter Splay CC:Custom-Min Qty:20pc	O:No Driver Z:0-10V Dimmable to 1% E:ELV Dimmable L:Lutron™ T:Lutron™ N:Non-Dimmable N:Non-Dimmable A:0-10V Dimmable to 1% +EM Backup F:ELV Dimmable +EM Backup M:Lutron™ U:Lutron™ Q:Non-Dimmable +EM Backup D:DALI	LEN:Fixture Length	O:No Accessories L:Canopy for On-Board Driver M:J-Box Cover N:Canopy for On-Board Driver + J-Box Cover	D:Dry IP 20

Specifications

This specification Grade LED downlight offers a wide selection of LED modules options to address design requirements in the spaces it illuminates. Many additional custom options are available; please contact manufacturer for details.

LED source

Tool-free field-replaced LED module. Proprietary high performance aluminum die cast heatsink for maximum LED life.

Optics

Computer-optimized reflector design. High reflected finish aluminum. Tool-free field-interchangeable reflectors and lens. 0-20°(O version), 0-40°(J version) vertical and 360° horizontal adjustment.

Body

Die-cast aluminum frame and body.

Trim

Die-cast aluminum CNC machine finished Minimal thickness. White can be field painted to match adjacent finishes

Fixture retention

Two torsion springs hold the fixture tight to the ceiling accommodating ceiling thickness fromm 1/16" to 1". Special springs for thicker ceiling available on request.

Life

Rated for 50,000 hours at 70% lumen maintenance.

Label

Etl listed for US Canada. CE labeled. CCC label available on request.

Warranty

5 years limited warranty.

Wet location

(if option is available ont and selected on page 1)

Sealed lens and integral silicon gasket behind the trim.

Dimming compatibility

Zaniboni fixture are compatible with all major dimming protocol in the industry. Please refer to zanibonilighting.com for general compatibility and wiring diagrams. Zaniboni recommends testing your unique dimming configuration as the exact full configuration (Dimmer, drivers, fixture quantities, voltage) may affect dimming performance.



N: Non-Dimmable

110-277V, 50/60Hz.


Economic solution for ON-OFF applications not requiring dimming.



E: ELV Dimmable

110-277V, 50/60Hz.


For ELV(Electronic Low Voltage) dimmers. Best for new construction application. Dims down to less than 10% light output(most cases). Consult dimming manufacturer for installation instructions. Must meet dimmer Minimum load Requirements.



Z: 0-10V Dimmable

110-277, 50/60Hz.


Prevalent solution on commercial projects. Integrates into a variety of building management and day lighting controls. Dims down to less than 10% light output(most cases). Must meet dimmer Minimum Load Requirements. Consult dimming manufacturer for installation instructions.



L: Lutron Hi-Lume A L3D

120-277V, 50/60Hz.

For 3-wire LUTRON dimming systems. Continuous dimming to 1% Consult dimming manufacturer for installation instructions.



T: Lutron Hi-Lume A LTE

120V, 50/60Hz.

For 2-wire Forward Phase Controls. Continuous dimming to 1% Consult dimming manufacturer for installation instructions.


N&E: Non-Dimmable & ELV Drivers

Measurements	LWH in mm	LWH in inches
7W - 9W - 13W	85.5 - 38 - 27.7	3.36" - 1.49" - 1.09"
18W - 26W	89 - 41 - 31.5	3.5" - 1.62" - 1.24"
36W - 50W	89 - 41 - 31.5	3.5" - 1.62" - 1.24"

N&E: Non-Dimmable & ELV Drivers


Measurements	LWH in mm	LWH in inches
7W - 9W - 13W	85.3 - 38 - 27.7	3.36" - 1.49" - 1.09"
18W - 26W	89 - 41 - 31.5	3.5" - 1.62" - 1.24"
36W - 50W	138 - 47 - 32	5.43" - 1.85" - 1.25"

Enclosures



A: Class 1, IC


For installation in ceilings with insulation. Driver "on board".



B: Class 1, Non-IC

For installation in ceilings with insulation. Driver "on board".


National or municipal codes must be followed regarding set back of thermal insulating material from fixture. Fixture are not designed for direct contact with thermal insulation.



D: Class 2, Non-IC

For installation on ceiling without insulation

National or municipal codes must be followed regarding set back of thermal insulating material from fixture. Fixture are not designed for direct contact with thermal insulation.



E: Airtight Enclosure


For installation where AT(Air-Tight) standards is required.

F: Chicago Plenum

Enclosure complies with Chicago Plenum requirements

G: Title 24 for Residential


Enclosure complies with California Title 24 requirements for specific residential applications. Please consult with your local inspector



R: Retro Fit-Enclosure


Available in assorted cutout sizes for easy installation of light fixture. For installation in plaster or t-bar ceilings.

National or municipal codes must be followed regarding set back of thermal insulating material from fixture. Fixture are not designed for direct contact with thermal insulation.



R: Retro Fit-Enclosure Coupled Wit Lutron HI-Lume Driver

When the Retro-Fit Enclosures is paired with any Lutron Driver, the Lutron Driver will be mounted atop the Retro-Fit enclosure with the line voltage connection inside the junction box.



R: Retro-Fit Mini

Used with our 1" aperture Lunas&Albas.

National or municipal codes must be followed regarding set back of thermal insulating material from fixture. Fixture are not designed for direct contact with thermal insulation.