

Rich Brilliant Willing

50 Greene St
New York NY 10013
T +1 212 388 1621
sales@richbrilliantwilling.com



pictured: AllSew 36 Square

AllSew

PENDANT | SCALABLE

Year Designed
2019

Description

AllSew is a new modular pendant tailored for workspaces, and equally suited for a wide range of residential, hospitality, and contract settings. Designed for tiled, large-scale installations, AllSew creates voluminous, architectural ceiling scapes for an impactful statement.

Country of Manufacture
USA

Materials
Sail cloth, fiber glass, aluminum

Finishes
See [Specification Logic](#)

Specification
30W standard power consumption
1700 lumens delivered

Lamping
(1) 30W LED
2000 Lumen Source
2700k CCT
min 80 CRI


LED Lifespan
50k hours

Certification
Pending

Dimensions
36" x 36" x 28" H

Cord Length
108 in / 274 cm SJT in white
Available in black

Canopy
Pending



| Model | |
|--------------|-----|
| AllSew | ALP |

| Size | |
|-------------|----|
| 36" | 36 |
| 48" | 48 |
| 72" | 72 |

| Profile | |
|----------------|----|
| Square | P1 |
| Diamond | P2 |

| Shade | |
|--|-----|
| White shade / white stitching / white trim | WWW |
| White shade / white stitching / black trim | WWB |
| White shade / custom stitching / white trim | WXB |
| White shade / custom stitching / black trim | WXW |
| Reclaimed sailcloth / custom stitching / custom trim | RXX |
| Custom | XX |

| Frame | |
|----------------|------|
| Matte White | PC20 |
| Matte Black | PC30 |
| Breccia | PC31 |
| Vermillion Red | PC42 |
| Buff | PC44 |
| Custom PC | PCXX |

| Variant | |
|------------------------------------|-----|
| Single direct output (2000 lumens) | LSD |

| Color Temp | |
|-----------------------|----|
| 2200K (candlelight) | 22 |
| 2700K (warm white) | 27 |
| 3000K (soft white) | 30 |
| 3500K (neutral white) | 35 |
| 4000K (cool white) | 40 |

| Input Voltage | |
|---|-----|
| 110 - 120V | 120 |
| 220 - 240V | 220 |
| 110-277V (universal -DL and -10 control only) | 277 |

| Control | |
|--|----|
| Flex TRIAC forward-phase* (1-100% dimming) | TM |
| Flex 0-10V analog* (1-100% dimming) | TM |
| Flex ELV reverse-phase* (1-100% dimming) | TM |
| Performance 0-10V analog* (0.1-100% dimming) | 10 |
| Performance DALI digital* (0.1-100% dimming) | DL |

*requires external power supply

| | | | | | | | | |
|------------|------|---------|-------|-------|---------|-----|---------|---------|
| ALP | - | - | - | - | - | - | - | - |
| model | size | profile | shade | frame | variant | CCT | voltage | control |

AllSew

Specification Logic

