

# Rich Brilliant Willing

50 Greene St  
New York NY 10013  
T +1 212 388 1621  
sales@richbrilliantwilling.com



pictured: smoke painted interior

## Dimple

SCONCE | FLUSH MOUNT

**Year Designed**  
2019

### Description

Dimple is a simple, contemporary option for a flush-mounted light, molded from solid glass and fit for installation in the ceiling or wall and is suitable for wet locations. The convex glass produces radial patterns that bend the light and are filled with bright and dark areas - light refracted within the thickness of the material of the cast glass.

### Materials

Cast glass, anodized aluminum

### Country of Manufacture

Made in China

### Specification

8.5W power consumption  
215 lumens delivered

### Lamping

(1) 8.5W LED  
640 lumen source  
min 80 CRI

### Dimensions


5.25 Ø × 3.2 in Depth  
13.4 Ø × 8.2 cm Depth

### Product Weight

2.5 lb / 1.14 kg


### Packaging

(1) 3.0 lb / 1.63 kg  
7 × 7 × 7 in  
18 × 18 × 18 cm



# Dimple

Specification Logic



<b>Model</b>	
Dimple	DP
<b>Shade</b>	
White	S1
Smoke	S2
Amber	S3
Frosted	S4
<b>Backplate</b>	
Natural	AA01
Black	AA04
Custom Powdercoat	PCXX
Custom Anodize	AAXX
<b>Color Temp</b>	
2200K (candlelight) (TRIAC 'TR' control only)	22
2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35
<b>Input Voltage</b>	
110-120V	120
220-240V	220
<b>Control</b>	
Standard TRIAC forward phase (10-100% dimming)	TR
*Flex 0-10V (1-100% dimming)	TM
*Flex TRIAC forward phase (1-100% dimming)	TM
*Flex ELV reverse phase (1-100% dimming)	TM
*External power supply location required (see below)	
<b>IP Rating</b>	
IP20	IP20
IP65	IP65
<b>External Driver</b> (Flex & Performance dimming only)	
External	DEX

DP	-	-	-	-	-	-	-
model	shade	backplate	CCT	input	control	IP rating	power supply