


# ENYO 2 D

RECESSED FIXED LED DOWNLIGHT



**ENYO 2 D - Recessed Fixed LED Downlight.** Enyo 2 D features SENSO-designed reflectors and a wide range of color temperatures in a high performance yet efficient and compact package. As part of the Enyo family of downlights, it's easy to get a cohesive design regardless of fixture size or style.

## Ordering Code

Fixture	<b>EN2D</b>								
	1	2	3	4	5	6	7	8	9
Driver		<b>EN2D</b>	--			--	--		
	1	2	3	4	5	6	7		

## Product Specifications

**SAMPLE:** Fixture **EN2D - FL - A90 - 615 - 25 - 07 - DL - 02 - 08** | Driver **910 - EN2D - FL - STD - 120 - A90 - 07**

1 - Model	2 - Trim	3 - LED	4 - Optic	5 - CCT	6 - Lumen	7 - Accessory	8 - Trim Color
<b>EN2D</b> · Enyo 2 Downlight	<b>FL</b> · Flanged	<b>A90</b> · Accuracy	<b>615</b> · 15° <b>630</b> · 30° <b>645</b> · 45° <b>660</b> · 60°	<b>25</b> · 2500K <b>27</b> · 2700K <b>30</b> · 3000K <b>35</b> · 3500K <b>40</b> · 4000K <b>65</b> · 6500K	<b>07</b> · 700 (7.7W) <b>10</b> · 1000 (10.9W) <b>15</b> · 1500 (16.8W) <b>20</b> · 2000 (25.7W)	<b>00</b> · No Accessory <b>DL</b> · Diffusing Lens <b>HO</b> · Honeycomb	<b>01</b> · White <b>02</b> · Black <b>08</b> · Silver <b>XX</b> · Custom

9 - Baffle Color	1 - Housing Style	2 - Model	3 - Trim	4 - Driver	Dim Level	Dim Level
<b>01</b> · White <b>02</b> · Black <b>08</b> · Silver <b>XX</b> · Custom	<b>910</b> · Remote <b>915</b> · New Construction <b>920</b> · IC Housing <sup>*1</sup>	Same as Fixture	Same as Fixture	<b>STD</b> · Non Dimming <b>LCS</b> · 0 - 10 Volt Protocol <b>DIM</b> · Phase <sup>*2/3</sup> <b>ELDOLC</b> · 0 - 10 Volt Protocol <b>ELDODA</b> · Dali Protocol	N/A 1% 1% 0.1% 0.1%	<b>LUTES</b> · Hilume Ecodigital <b>LUT2W</b> · 2 Wire for phase <sup>*3</sup> <b>LUT5S</b> · 5 Series Eco System <b>DMX</b> · SENSO <sup>*4</sup> <b>EMG</b> · Emergency Driver <sup>*4/5</sup>

5 - Voltage	6 - LED	7 - Lumen
<b>120</b> · 120V <b>277</b> · 277V <b>347</b> · 347V	Same as Fixture	Same as Fixture

\*1 Cannot exceed **1500lm**  
\*2 Not available in **700lm**  
\*3 120V only  
\*4 Requires remote housing  
\*5 Specified separately

Project : \_\_\_\_\_  
Quantity : \_\_\_\_\_  
Type : \_\_\_\_\_  
Notes : \_\_\_\_\_  
\_\_\_\_\_

# ENYO 2 D

RECESSED FIXED LED DOWNLIGHT

## Light Engine

- Output:** up to 2000lm
- High Efficacy:** up to 150 lumen/Watt
- Color Options (CCT):** 2500K, 2700K, 3000K, 3500K, 4000K or 6500K
- Color Consistency:** Range within a 3-MacAdam Ellipse
- Color rendering (CRI):** 90 CRI & 50+ R9 Value

## Driver

- Dimming:** 1% dimming standard with 0.1% option
- Ripple:** Industry leading Low ripple
- Efficiency:** Power Factor >0.9  
Efficiency over 85%  
Class 2 output for safety
- Installation:** Small Footprint allows retrofit installations


## Installation

- For new and retrofit installations
- Simple connection between fixture and driver via quick connect

## Construction / Finish


- High quality, scratch resistant powder coated finish in standard, premium or custom colors
- Cast Aluminum Trim
- Made in Canada

## Dimensions




## Accessories

### Diffusing Lens



### Honeycomb Mesh







# ENYO 2 D

RECESSED FIXED LED DOWNLIGHT



## Housing Options

### Standard Senso Housing - 910





### Included

Unless specified otherwise, this is provided as standard

- Driver with enclosure**
  - Galvanized steel enclosure
- Installation**
  - Laying on top of ceiling
  - Remote from fixture



### New Construction - 915



### Included

- Plaster Frame**
  - Galvanized steel construction with cut-out
- Bar hanger**
  - Length: from 14-3/16" to 26"
- Outlet Box**
  - Outlet Box Included

### IC Housing - 920



### Included

- IC Housing**
  - Galvanized steel construction
  - Airtight
  - Includes gasket prepped junction box
- Plaster Frame**
  - Galvanized steel construction
- Bar hanger**
  - Length: from 14-3/16" to 26"

**Note:** use only with LED modules up to 1500lm

